

# HGC ORDER FORM



## HELIX GROOVE CLEANERS ORDER FORM

Approved by: \_\_\_\_\_

**Required order information** \* Require All information below to Mfg. & Quote.

- \* \_\_\_\_\_ Manufactures Wire Rope Diameter  
Do not convert to inches or millimeters.  
\_\_\_\_\_ Wire Rope Measured Diameter by Caliper if available.
- \* \_\_\_\_\_ Number of OUTER STRANDS (See rope photos below)  
\_\_\_\_\_ With Wear Plate Installed (Optional)

**ROPE TYPE OUTER STRANDS:**

- \*  Triangular or Swaged Strand (See Drawing Below)
- \*  Round Strand or Round Flattened Strand (See Drawing Below)
- \*  Hyfil K8, Turboplast, Supperplast8, Eurolift (See Drawing Below)

**LEFT LAY or RIGHT LAY:** (See rope photos below)





- \*  Right Lay
- \*  Left Lay

\* \_\_\_\_\_ Lay Length **REQUIRED** as these are Custom made and non-refundable. Information received by Corelube Equipment must be accurate. Send the wire rope Manufacturers Data Sheet if available.



### Outer Strand Construction Examples

Groove Cleaners can be ordered from 3 to 18 Outer Strands.

|   |  |  |   |
|---|--|--|---|
| <p>Round Strand</p>  <p>6 Outer Round Strand</p> | <p>Round Flattened Strand</p>  <p>16 Outer Round Strand</p> | <p>Triangular, Swaged Strand</p>  <p>6 Outer Triangular Strand</p> | <p>Hyfil K8, Turboplast, Superplast, Eurolift</p> <p>Large Shallow Gaps Between Strands</p>  <p>8 Outer Round Strand</p> |
|---|--|--|---|

